




































Suitable connectors for hoses and pipes

Type of pneumatic line	Pressure nominal at 20 °C	Quick union QV 8 brass -07 	Quick union QV 8 stainless steel -08 	Hose nipple S 4/6 plastic, stainless steel -00 	Compression ferrule KV 8 (MS) brass -04 	Compression ferrule KV 8 (VA) stainless steel -06 	Compression ferrule KV 8 (PVDF) -19 	Flared union BV 6 brass -09 	Flared union BV 6 stainless steel -11 	Swage-lock 12 mm stainless steel -21 
Polyamide (PA) hose 8/6 mm 	Pmax at 60 °C = 12 bar	yes 	yes 		yes support sleeve provided 	yes support sleeve provided 	yes up to 10 bar 			
PVC hose 10/6 mm 	PN on request			yes 						
PVC hose, reinforced 12/6 mm 	PN on request			yes 						
PTFE hose 8/6 mm 	PN 4	yes 			yes support sleeve provided 	yes support sleeve provided 	yes 			
Copper pipe 8/6 mm 	PN on request				yes 					
Copper pipe 6/4 mm 	PN on request							yes flare tool needed 		
Stainless steel pipe 6/4 mm 	PN on request								yes flare tool needed 	
Stainless steel pipe 8/6 mm 	PN on request					yes 				
Stainless steel pipe 12/10 mm 	PN on request									yes 